ESET Tech Center

Knowledgebase > Legacy > I receive the error message "Cannot init openssl library" when installing ESET File/Mail/Gateway Security for Linux

I receive the error message "Cannot init openssl library" when installing ESET File/Mail/Gateway Security for Linux Ondersteuning | ESET Nederland - 2025-03-07 - Comments (0) - Legacy

https://support.eset.com/kb3584

Issue

You see one of the following error messages in the log files or in the Terminal when installing ESET File/Mail/Gateway Security for Linux:

```
Cannot init openssl library
Child process wwwi[PID] terminated with return
code 73, won't be restarted
Child process wwwi[PID] did not handle signal 6,
restart in 0 seconds
```

Details

Solution

For ESET File/Mail/Gateway Security for Linux to work properly, you need to have OpenSSL installed.

If you are using a 64-bit edition of Linux distribution, it is necessary to have both the 32-bit and 64-bit versions of <u>OpenSSL</u> installed on your server. In some cases, development OpenSSL package variants are required.

To search and install a suitable OpenSSL package for your system, use one of the following commands in the Terminal:

Debian-based (apt)	Search: apt-cache search openssl Install*: apt-get install openssl libssl-dev
Red Hat-based (yum)	Search: yum search openssl Install*: yum install openssl openssl-devel

Install openssl using distribution-like package software or
compile OpenSSL from the source using one of the <u>tarballs</u> .

* OpenSSL packages may have different names in various Linux distributions.

If you are still unable to resolve your issue, please $\underline{\mathsf{email}}$

ESET Technical Support.

Tags Linux