

# ESET Tech Center

Kennisbank > Legacy > Legacy ESET Remote Administrator (6.x / 5.x / 4.x) > 5.x > How do I disable password protection on client workstations? (5.x)

---

## How do I disable password protection on client workstations? (5.x)

Ondersteuning | ESET Nederland - 2024-08-28 - Reacties (0) - 5.x

<https://support.eset.com/kb3090>

### Issue

---

Disable password protection on client workstations using ESET Remote Administrator, or on individual client workstations

### Solution

---

If you do not use ESET Remote Administrator to manage your network

[Perform these steps on individual client workstations.](#)

### Disable password protection on client workstations using ESET Remote Administrator

1. Open the ESET Remote Administrator Console (ERAC) by double-clicking the ERAC icon on your Desktop or by clicking **Start** → **All Programs** → **ESET** → **ESET Remote Administrator Console** → **ESET Remote Administrator Console**.
2. In the ERAC, click **Tools** → **Policy Manager**.
3. Select your default server policy and click **Edit**.
4. In the **Configuration Editor** window, expand **Windows desktop v5** → **Kernel** → **Settings** → **Protect setup parameters**.
5. Click **Password to unlock** and then click **Set Password**.



### Figure 1-1

Click the image to view larger in a new window

6. In the **Password** window, click **Delete** and then click **OK**.



### Figure 1-2

7. Click **Console** and click **Yes** when prompted to save your changes. These changes will take effect the next time client workstations assigned to this policy check in to the ESET Remote Administrator Server.

---

## Disable password protection on individual client workstations

1. Open ESET Endpoint Security or ESET Endpoint Antivirus. [How do I open my ESET product?](#)
2. Press the **F5** key to open the Advanced setup window.
3. Expand **User interface**, click **Access setup**, and then deselect the check box next to **Password protect settings** (you will be required to provide the current security password in order to disable this feature).
4. Click **OK** to save your changes.



### Figure 2-1

Click the image to view larger in new window

Tags  
ERA 5.x